



p.c.b. layout

Approvals



15A-300V



15A-630V

Electrical

Rated voltage	450V
Rated current	20A
Contact resistance	20mΩ
Insulation resistance	500MΩ/DC500V
Withstanding voltage	AC2000V/1min
Wire range	

Torque	
Temp. Range	-40°C +105°C
Stripping length	
Max sold. time	+250°C for 5 sec

Dimensions

Pitch	7,62 mm
Poles	2÷22

Material

Housing	PA66 UL94V0
Pin	Copper Alloy, Sn plated
Cage	
Screws	
Side Block	
Nut screw	
Clamp	

3.90

General description of ordering code

Series	n. Poles	Pitch	Version	Color	Custom
CCM	02÷22	-7.62	-VF		

Version	Date
01/23	05/07/23



euro-block



linear dimension (Tolerances Standard GB/T 14486-2008)										UNITS: mm
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	SCALE: 10:1
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	SHEET SIZE: ISO A4



First angle projection

CCM-7.62-VF