



2m USB 3.2 Type A to B Cable, 5Gbps, Cromo Line

No.: 36662

USB Type A Male to B Male

Description

Superior performance and design USB 3.2 Gen 1 Type A to B cable for public facing and design focused commercial and home applications

SuperSpeed USB - supports data transfer speeds up to 5Gbps (USB 3.2 Gen 1, USB 3.1 Gen 1, USB 3.0)

Chrome design ABS housing, 24K gold plated connectors and contacts

Triple shielded cable, corrosion resistant, high performance tinned copper conductors

10 year warranty

The Cromo Line USB 3.2 Type A to B cables from Lindy's Cable Lines concept are high-performance, fully-featured and design-oriented connectivity solutions, combined with the highest quality construction materials and distinctive connector architecture.

Cromo Line USB 3.2 cables feature triple shielded construction with tinned copper conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

USB bandwidths up to 5Gbps are supported for rapid transfer of large data volumes.

Cromo Line USB 3.2 Type A to B cables are available in the following lengths: 0.5m, 1m, 2m, 3m and 5m.

We have adapted the naming of our USB 3 cables to follow the updated USB specification.

USB 3.0 and USB 3.1 Gen 1 have been renamed to USB 3.2 Gen 1, supporting data transfer up to 5Gbps

USB 3.1 and USB 3.1 Gen 2 are now called USB 3.2 Gen 2, supporting data transfer rates up to 10 Gbps

USB 3.2 Gen 2x2 is a new standard, supporting data transfer rates up to 20 Gbps

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

Technical details

Connectors

Connector A: USB 3.2 Type A Male

Connector B: USB 3.2 Type B Male

Housing Material: Chrome Plated, ABS

Shielding in head shell: Tinplate

Connector Plating: Gold 1µm

Pin Construction: Brass

Pin Plating: Gold 3µm

Dimensions (approx.) WxDxH:
A: 16x35x8.3mm [0.63x1.38x0.34in]
B: 13x37x14.3mm [0.51x1.45x0.56in]

Cable Construction

Length: 2m [6.56ft]
Standard: USB 3.2 Gen 1 [USB 3.1 Gen 1, USB 3.0]
Power Delivery: -
Colour: Grey
Type: Round
Jacket Diameter: 5.5mm [0.22in]
Jacket Material: PVC
Conductor Material: Tinned Copper
Conductor Gauge Power: 24AWG
Conductor Gauge Data: 28AWG
Shielding: Tinned Copper Braid 65%

Specifications

Supported Bandwidth: 5Gbps
Maximum Resolution: -
Nominal Attenuation: 0.5MHz - 7.5GHz < 25dB
Minimum Band Radius: 55mm [2.2in]
Operating Temperature: -20°C - 80°C [-4°F - 176°F]
Storage Temperature: -25°C - 85°C [-13°F - 185°F]

Miscellaneous

Packaging Type: Polybag
Warranty (Years): 10
Product Compliance: RoHS, REACH, California Proposition 65 & UL

Purchasing Information

No.: 36662
EAN: 4002888366625

This product is also available in other lengths

36660 - 0.5m [1.64ft]
36661 - 1m [3.28ft]
36662 - 2m [6.56ft]
36663 - 3m [9.84ft]
36664 - 5m [16.40ft]