

Approvals



15A - 300V

Electrical

Rated voltage 300V  
 Rated current 15A  
 Contact resistance 20mΩ  
 Insulation resistance 500MΩ/DC500V  
 Withstanding voltage AC1600V/1min  
 Wire range 26-14 AWG 1,5mm<sup>2</sup>

Torque  
 Temp. Range -40°C +105°C  
 Stripping length 5 mm  
 Max sold. time +250°C for 5 sec.

Dimensions

Pitch 5,08 mm  
 Poles 2÷24

Material


Housing PA66 UL94V0  
 Pin Copper Alloy, Sn plated  
 Cage Stainless steel  
 Screws  
 Side Block  
 Nut screw  
 Clamp

General description of ordering code



Series	n. Poles	Pitch	Version	Color	Custom
MRM6	2÷24	-5.08	-V		

Version Date

01/23 07/11/23



p.c.b. layout



euro-block



linear dimension (Tolerances Standard GB/T 14486-2008)										
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

UNITS: mm

SCALE: 10:1

SHEET SIZE: ISO A4



First angle projection

MRM6-5.08-V