



euroclamp

Se

Search

VIP log-in

You are here: [Home](#) / Product View

MVS15_-5,08-V

Single-deck terminal block - Modular version - Pitch 5,08mm - 2÷12 poles



GENERAL INFORMATION

Pitch	5,08 mm
Height	13.2 mm
Depth	8.9 mm
Dimensional class	Bassa



Wire section	1.5 mm ² / 16 AWG
Clamp opening size	2.5 x 2.1 mm
Wire stripping	max 7 mm
Operating temperature	-40 ÷ +130 °C

ELECTRICAL CHARACTERISTICS

Current	17.5 A
Voltage	450 V
test voltage	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

Screw Type	Imperdibile
Recommended torque	0.5÷0.55 Nm / 4.5÷4.9 in.lbs

APPROVALS DATA

			
Current	17.5 A	-	17.5 A factory / 10 A field
Voltage	450 V	-	300 V
Wire section	1.5 mm ²	-	16 ÷ 30 AWG
Torque	0.5 Nm	-	4.5 Lb-in
FILE	CA02.00598	-	E178356

MATERIALS

Housing	PA - UL 94 V0
Screw	M3
Clamp	Nickel-plated copper alloy
Terminal	Tin-plated copper alloy
Scip Number	713ad43e-8dff-4607-9cfa-843d4a730153



COLOURS	
Standard	On request
	

POLES	NAME	3DFILE
2	MVS152-5,08-V	N/A
3	MVS153-5,08-V	N/A
4	MVS154-5,08-V	N/A
5	MVS155-5,08-V	N/A
6	MVS156-5,08-V	N/A
7	MVS157-5,08-V	N/A
8	MVS158-5,08-V	N/A
9	MVS159-5,08-V	N/A
10	MVS1510-5,08-V	N/A
11	MVS1511-5,08-V	N/A
12	MVS1512-5,08-V	N/A

